

Geocomposite Drainage Nets provide a variety of benefits including their light weight, quality-controlled construction, easy installation and serving as an environmentally friendly solution to traditional drainage materials. Drainage Nets are composed of a three dimensional bi-planer Geonet, laminated to a non-woven Geotextile which serves as both a cushion and filter to prevent the net from clogging. These products come in a very wide variety of thicknesses and Geotextile combinations with custom products available.

- Erosion control
- Landfill Leachate Collection
- Caps and Closures
- Pond Leak Detection
- Foundation Wall Drainage
- Leak Detection
- Methane Gas Collection
- Roadway and Pavement Drainage

### Certified Properties

### ASTM

GEONET			
Thickness (mil)	D-5199	250	250
Carbon Black (%)	D-4218	2.0	2.0
Tensile Strength (lb/in)	D-7179	55	55
Melt Flow (g/10 min)	D-1238	1.0	1.0
Density (g/cm <sup>3</sup> )	D-1505	0.94	0.94
Transmissivity (gal/min/ft (m <sup>2</sup> /sec))	D-4716	14.50 (3.0x10 <sup>-3</sup> )	14.50 (3.0x10 <sup>-3</sup> )
<b>GEOCOMPOSITE</b>		<b>6 oz/yd<sup>2</sup></b>	<b>8 oz/yd<sup>2</sup></b>
Ply Adhesion (lb/in)	D-7005	1.00	1.00
Transmissivity DS (gal/min/ft (m <sup>2</sup> /sec))	D-4716	<b>TN 270-2-6</b>	<b>TN 270-2-8</b>
		2.42 (5.0x10 <sup>-4</sup> )	2.42 (5.0x10 <sup>-4</sup> )
Transmissivity SS (gal/min/ft (m <sup>2</sup> /sec))	D-4716	<b>TN 270-1-6</b>	<b>TN 270-1-8</b>
		7.25 (1.5x10 <sup>-3</sup> )	7.25 (1.5x10 <sup>-3</sup> )
<b>GEOTEXTILE</b>			
Fabric Weight (oz/yd <sup>2</sup> )	D-5261	6	8
Grab Tensile (lb)	D-4632	160	225
Grab Elongation (%)	D-4632	50	50
Trapezoid Tear (lb)	D-4533	65	90
CBR Puncture (lb)	D-6241	450	600
Water Flow (gpm/ft <sup>2</sup> )	D-4491	125	100
Permittivity (sec <sup>-1</sup> )	D-4491	1.63	1.26
Permeability (cm/sec)	D-4491	0.30	0.30
AOS (US Sieve)	D-4751	70	80